



# LABELLE SUPPLY CO. LTD.

Serving the shoe trade since 1948

7278 Curragh Avenue, Burnaby, British Columbia, Canada V5J 4V9  
Tel: 604-253-6301 **Toll Free: 1-800-663-9893** Fax: 604-253-7253  
Website: <https://labellesupply.com>



## Vibram 7510 Rock Sheet



A sheet produced in Vibram® Grip compound, is ideal for the diecutting of the side strips used for free climbing shoes.  
Recommended for special applications where extreme grip is required, such as inserts for gloves, prosthetics and supports.



Code	Thickness
292575018	1.8 mm
292575135	3.5 mm
292575150	5 mm

- Compound: GRIP
- Sizes: 93X64 cm



## Vibram 7509 Grip Branded




This sheet branded with the Vibram script, makes it ideal for the resoling of free climbing shoes. Recommended for special applications where extreme grip is required, such as inserts for gloves, prosthetics and supports.



Code	Thickness
292575035	3.5 mm
292575050	5 mm

- Compound: GRIP
- Sizes: 93X64 cm



## Vibram 7507 XSGrip Sheet




A new softer rubber compound engineered for free climbing shoes that provides a higher level of grip in both the heat and the cold. Excellent adherence/grip ratio on micro holds.



Code	Thickness
292577035	3.5 mm
292577040	4 mm
292577050	5 mm

- Compound: XSGRIP
- Sizes: 93X64 cm



## Vibram 7130 Boulder Sheet



A sheet produced in extra soft rubber compound Vibram® Idrogrip with the new Vibram suction design. Ideal for die-cutting soles and inserts, and for the repair and production of approach shoes. Perfect material to use when traction and grip is required on uneven wet surfaces. Excellent for water sports.



Code	Thickness
292576045	4.5 mm

- Compound: IDROGRIP (Grip on Wet)
- Sizes: 93X64 cm



## Vibram 7530 XSEdge Sheet



A Vibram climbing compound that allows weight to be concentrated on even the smallest holds. Thanks to its improved resistance to plastic deformation, Vibram® XS Edge keeps its shape even after repeated use in all climate conditions.



- ✓ new compound for climbing
- ✓ designed for outdoor climbing and bouldering
- ✓ excellent compromise between performance and wear
- ✓ ensures maximum support on the smallest holds
- ✓ keeps its shape at both low and high temperatures



Code	Thickness
292579040	4 mm
292579050	5 mm

- Compound: XSEGE
- Sizes: 93X64 cm



## Vibram 7509 XSFlash Sheet




A sheet developed with a new Vibram non-marking compound which provides maximum grip on artificial footholds and leaves indoor walls clean. Extremely sticky compound, designed for artificial holds. Non marking compound: keeps walls and holds clean.



Code	Thickness
292578050	5 mm

- Compound: XSFLASH
- Sizes: 93X64 cm



\* Was yellow: Vibram has switched to Grey.

Toll Free: 1-800-663-9893

\*All volume prices are based on same size, thickness and colour, except volume assorted prices: same group.